



A126

Cascade Jewel Take Me Anywhere Cardigan



Designed By Susie Bonell

Jewel Take Me Anywhere Cardigan

By Susie Bonell

Materials: Cascade Yarns Jewell Hand Dyed: 8, 9, 10 skeins of #9620

Needles: size 8 & 9

6 buttons

Gauge: 4 sts = 1", 5 rows = 1" in st st

Finished Measurements: 39" (43", 47")

8 Stitch Cable Panel (over 12 sts) Stockinette Stitch (st st)

Pattern Note: Some models were knit on larger needles and have a 3 sts ridge at front edges, rather than 4 as per the pattern.

Row 1, 5, 7: P2, K8, P2 Repeat.

Row 2, 4, 6, 8: (wrong side) K2, P8, K2.

Row 3: P2, C8B, P2. C8B = slip next 4 sts onto cable needle and hold in back, knit next 4 sts from L needle, knit 4 from cable needle. Repeat rows 1-8 for pat.

Lace Panel (9 stitches)

Row 1: K2, K2tog, YO, K1, YO, SSK, K2. PM = place marker

Row 2: (and all wrong side rows) Purl.

Row 3: K1, K2tog, YO, K3, YO, SSK, K1.

Row 5: K2tog, YO, K5, YO, SSK.

Row 7: K3, YO, sl 2 k-wise, K1, P2sso, YO, K3.

Row 8: Purl.

Repeat rows 1-8 for pat.

Back

With size 8 needles, cast on 75, 85, 91 sts. Work in K1, P1 ribbing for 2 ½" increasing to 85, 93, 101 sts on last wrong side row. Change to larger needles and establish pattern as follows: K5 (K9, K13) st st PM, Row 1 cable panel (12 sts), PM, Row 1 Lace Panel (9 sts), PM, Row 1 cable panel (12sts), PM, Row 1 Lace Panel (9 sts), PM, Row 1 Cable Panel (12 sts), PM, Row 1 Lace Panel (9 sts), PM, Row 1 Cable Panel (12 sts), K5(K9, K13) st st. Continue working as established until back measures 15 ½", 16", 16 ½" or desired length to underarm.

Armhole Shaping

Bind off 6 (8, 8) sts at the beg of the next two rows. Continuing in patterns, dec 1 st each side every other row 5(7, 7)times. Work until armhole measures 9 ½", 10", 10 ½".

Shoulders

Bind off 5 (5, 6) sts on next 4 rows. Bind off 6 (6, 7) sts next 2 rows. Bind off remaining.

Right Front

With size 8 needles, cast on 38 (43, 45) sts. Work in K1, P1 ribbing for 2 ½" increasing to 43, (47, 51) sts on last wrong side row. Change to larger needles and establish pattern as follow: K5 (9, 13) st st, PM, Row 1 of Cable Panel (12 sts), PM, Row 1 of Lace Panel (9 sts), PM, Row 1 of Cable Panel (12 sts), PM, K5 (K5, K5) st st. Work as established to armhole as for back, Work armhole shaping as for back at armhole edge. Continuing in pattern work until armhole meas-

ures 6 ½" (all sizes) and at NECK EDGE bind off 8 (9, 9) sts, then dec 1 st every other row 7 (7, 8) times. Continue until front measures same as back to shoulders and work shoulder shaping as for back.

Repeat for Left front reversing shaping.

Sleeves

With size 8 needles, cast on 36 (38, 41) sts. Work in K1, P1 ribbing for 2 ½" increasing to 41, (43,47) on last wrong side row. Change to larger needles and establish patterns as follows: K4 (5, 7) st st ,PM, Row 1 of Cable Panel (12 sts), PM, Row 1 of Lace Panel (9 sts), PM, Row 1 of Cable Panel (12 sts), K4 (K5, K7) st st. Work patterns as established while working the increases in st st as follows: Inc 1 st each side every 4th row 17(13, 18) times, then every 6th row 1, 4, 1 times. Work until sleeves measures 17 ½" (18 ½", 18 ½") or desired length to armhole.

Cap Shaping

Bind off 6 (8, 8) sts on next 2 rows. Dec 1 st each side every other row 5 (7, 7) times. Dec 1 st every row 8, 1, 7 times. Dec 1 st every 2nd row 7, 9, 7 times. Bind off 3 sts at the beg of next 4 rows. Bind off remaining.

Work 2nd sleeve the same.

Steam and shape pieces as necessary. Sew shoulder seams.

Neck Trim: With smaller needles and right side facing you, pick up and knit 8 (9, 9) bound off sts, 11 (13, 14) sts from side neck 30(32, 34) sts from back 11(13, 14) from other side neck, 8(9, 9) from bound off sts. Work in K1, P1 ribbing for 6 rows. Bind off in pattern.

Left Front Trim: With smaller needles and right side facing you pick and knit 98 (100, 102) sts and work in K1, P1 ribbing for 6 rows and bind off in pattern. Mark placement for 6 buttons.

Right Front Trim: Work as for Left Front working buttonholes corresponding to markings on rows 3 and 4 of trim as follows: On row 3: bind off 2 sts, on row 4 cast on 2 sts above bound off sts to complete buttonhole.

Sew in sleeves. Sew side seams. Weave in all ends. Steam again if necessary.