



W419

Venezia Worsted Lace Shoulderette



Designed by Kristen Stoltzfus

Venezia Worsted Lace Shoulderette

By Kristen Stoltzfus

Materials:

Cascade Yarns Venezia Worsted 70% merino wool/30% silk (worsted weight) yarn, (100g/3.5oz/219oz per hank)

-5 hanks #174

size G/6/4mm hook, or size needed to obtain gauge

yarn needle

rust proof pins

Skill Level:

Easy

Gauge:

7 repeats of Rows 2-3=6 in.

Finished Size:

18 ½ in. by 44 in.

Special Stitches:

V stitch (V st)=(dc, ch 2, dc) in same st

Pattern Notes:

Shoulderette is worked from the center out in two panels. Edging is worked in rows on long sides of panels. The ends are then slip stitched together to make cuffs.

First ch 3 counts as first dc throughout.

Shoulderette:

First Panel:

Ch 86

Row 1: V st in 6th ch from hook, (ch 1, sk 3 chs, V st in next ch) across to last 2 chs, sk next ch, dc in

last ch; ch 1, turn. 20 V sts, 2 dc

Row 2: RS sc in first dc, work (2 sc, ch 3, 2 sc) in V st, [sc in ch 1 sp, (2 sc, ch 3, 2 sc) in next V st] across, sc in last dc; ch 3, turn. 20 ch 3 lps

Row 3: (V st in ch 3 lp, ch 1) across to last ch 3 lp, V st in last ch 3 lp, dc in last sc; ch 1, turn.

Rep Rows 2-3 until piece measures 22 in. or is 4 in. past your elbow when held with foundation ch in the center of your back. End with Row 2. Fasten off.

Second Panel:

With WS facing, join yarn on opposite side of foundation ch across from first dc.

Row 1: ch 3, V st across from V st, (ch 1, V st across from V st) across to last 2 chs, dc in first ch of turning ch; ch 1, turn. 20 V sts, 2 dc

Rep Rows 2-3 of First Panel until Second Panel has the same amount of rows. Do not fasten off.

Edging:

Row 1: turn, sl st into side of first dc, ch 4, 3 tr in same st, work 4 tr in side of each dc across; ch 3, turn.

Row 2: work tr in each of next 3 tr, retaining last lp of each tr on hook, yo, draw through all 4 lps on hook to make tr cl, (ch 3, work tr in each of next 4 tr, retaining last lp of each tr on hook, yo, draw through all 5 lps on hook to make tr cl) across; ch 1, turn.

Row 3: sl st into next st (center of tr cl), (ch 5, sl st, ch 7, sl st, ch 5, sl st) in same st, [work 2 sc over ch 3 lp, sl st into next center of tr cl, (ch 5, sl st, ch 7, sl st, ch 5 sl st) in same st] across. Fasten off.

Join yarn on remaining long side in first side of first dc, with RS facing. Rep Edging.

Mist with cool water and pin to measurements, putting pin in each ch 7 lp of long side of Edging to open Edging.

Cuff (make 2):

Hold long sides WS together and sl st through both layers on base of Row 2 of Edging for 5 in. from end. Fasten off, weave in all ends.