Maggie Hoodie

Cascade 220®

Designed by Melissa Leapman

Knitting Pattern W910 - Intermediate

Finished Size:

Small (Medium, Large, 1X, 2X)

Materials:

- Cascade Yarns® Cascade 220®: 100% Peruvian Highland Wool; 100 g (3.5oz) / 220 yds (200 m); 8 (9, 9, 10) skeins color #2445 Shire
- US 10 (6.0 mm) knitting needle, or size needed to obtain gauge
- US 10 (6.0 mm) double pointed knitting needles (DPNs)
- 2 Stitch holders
- Yarn needle
- 6 - 1 1/8" buttons

Finished Measurements:

Bust (buttoned): 36 (40, 44, 48, 52)"

Total length: 26 (26 ½, 26 ½, 27, 27)"

Gauge:

20 sts x 24 rows = 4" (10 cm) in Eyelet Cable Patt

Eyelet Cable Pattern (over mult 5 + 2 sts)

Row 1 (RS): P2, *slip next 3 sts purlwise onto the RH needle, pass the 3rd st on the RH needle over the first 2 sts as if you're binding it off, slip those 2 sts back onto the LH needle, K1, yarn over, K1, P2. Repeat from * across.

Row 2 and all WS rows: K the K sts and P the P sts, and P the yarn over sts.

Row 3: P2, *K3, P2. Repeat from * across.

Row 4: As Row 2.

Repeat Rows 1-4 for patt.

Abbreviations:

CO = Cast on

Cont = Continue

K = Knit

K2tog = Knit 2 stitches together

LH = Left hand

P = Purl

Patt = Pattern

RH = Right hand

SSK = Slip, slip, knit the two slipped stitches together

St(s) = Stitch(es)

Thank you for downloading our free pattern. Find us online at https://www.cascadeyarns.com or on social:

All images, text and illustration(s) © Cascade Yarns® 2025

Reverse Stockinette Stitch Pattern

Row 1 (RS): Purl across.

Row 2: Knit across.

Repeat Rows 1 and 2 for patt.

Note: Instructions include one selvedge stitch each side; these stitches are not reflected in final measurements.

Begin Pattern:

Back:

CO 92 (102, 112, 122, 132) sts.

Beg Eyelet Cable Patt, and work even until piece measures approx 16 ½" from beg, ending after WS row.

Shape Armholes:

BO 10 (15, 15, 20, 20) sts at beg of next two rows–72 (72, 82, 82, 92) sts rem.

Cont even in patts as established until piece measures approx 25 (25 ½, 25 ½, 26, 26)" from beg, ending after WS row.

Shape Shoulders:

BO 6 (6, 8, 8, 10) sts at beg of next four rows, then BO 7 (7, 8, 8, 9) sts at beg of next two rows–34 sts rem. BO all sts.

Pocket Linings (make two)

CO 18 sts.

Beg Reverse Stockinette St Patt, and work even until piece measures approx 6" from beg, ending after a knit (WS) row, inc 4 sts evenly across last row–22 sts.

Left Front:

CO 52 (57, 62, 67, 72) sts.

Beg Eyelet Cable Patt, and work even until piece measures approx 6" from beg, ending after WS row.

Place Pocket Linings:

Work patt as established across first 10 sts, slip next 22 sts onto holder, work patt as established across 22 sts from pocket lining holder (with the purl side up), work patt as established across to end row.

Cont even until piece measures approx 16 ½" from beg, ending after WS row.

Shape Armhole:

BO 10 (15, 15, 20, 20) sts at armhole edge–42 (42, 47, 47, 52) sts rem.

Cont even in patts as established until piece measures approx 23 (23 ½, 23 ½, 24, 24)" from beg, ending after RS row.

Shape Neck:

Work across first 10 sts and slip them onto a holder, work across to end row.

BO 4 sts at neck edge once, BO 3 sts at neck edge once, BO 2 sts at neck edge once, then dec 1 st at neck edge every row four times–19 (19, 24, 24, 29) sts rem.

Cont even until piece measures same as back to shoulders.

Shape Shoulder:

BO 6 (6, 8, 8, 10) sts at shoulder edge twice.

Work one row even.

BO rem 7 (7, 8, 8, 9) sts.

Place markers for 6 buttons, making the first one ½" down from beg of neck shaping, the last 3" from lower edge, and the others evenly-spaced in between.

Right Front:

Same as left front except reverse all shaping and make buttonholes opposite marker on RS row as follows: Work first 5 sts in patt as established, BO next 2 sts, work across

All images, text and illustration(s) © Cascade Yarns® 2025

to end row. On subsequent row, CO 2 sts over the bound off sts.

Sleeves:

CO 47 sts.

Beg Eyelet Cable Patt, and inc 1 st each side every other row 0 (0, 0, 4, 4) times, every fourth row 5 (14, 17, 21, 21) times, then every sixth row 15 (8, 5, 0, 0) times, working new sts into patt as they accumulate–87 (91, 91, 97, 97) sts.

Cont even until piece measures approx 21 ¼ (21 ¼, 20 ¼, 20 ¼, 20 ¼)" from beg, ending after WS row.

BO.

Finishing:

Sew shoulder seams. Lightly block pieces.

Hood:

With RS facing, pick up and work patt across 10 sts from right front holder, place marker, pick up and purl 64 sts around neckline, pick up and work patt across 10 sts from left front holder–84 sts.

Keeping 10 sts each side in Eyelet Cable Patt and all other sts in Reverse Stockinette st, work even until hood measures approx 1", ending after purl row. Place a marker to set off the two middle sts in the center back of neck.

Next Row (WS): Cont patts as established across to first marker, M1 knitwise, K2, M1 knitwise, work patts as established to end row–86 sts.

Work even in patts as established for five rows.

Next Row (WS): Cont patts as established across to first marker, M1knitwise, K2, M1 knitwise, work patts as established to end row–88 sts.

Work even in patts as established for five rows.

Next Row (WS): Cont patts as established across to first marker, M1 knitwise, K2, M1 knitwise, work patts as established to end row–90 sts.

Work even in patts as established until hood measures approx 12" from beg, ending after WS row.

Next Row (WS): Cont patts as established across to 2 sts before first marker, K2tog, K2, SSK, work patts as established to end row–88 sts.

Work even in patts as established for one row.

Next Row (WS): Cont patts as established across to 2 sts before first marker, K2tog, K2, SSK, work patts as established to end row–86 sts.

Work even in patts as established for one row.

Next Row (WS): Cont patts as established across to 2 sts before first marker, K2tog, K2, SSK, work patts as established to end row–84 sts.

Work even in patts as established for one row.

Next Row (WS): Cont patts as established across to 2 sts before first marker, K2tog, K2, SSK, work patts as established to end row–82 sts.

Divide rem sts onto two double-pointed needles, putting 41 sts onto each one, and holding WS facing each other, graft them tog.

Pocket Edgings:

With RS facing, pick up and K 22 sts from pocket holder. Work Garter St (knitting all rows) until edging measures approx 1". BO.

Sew pocket linings to WS of fronts. Sew sides of pocket edgings to RS of front. Sew underarm and side seams. Sew on buttons opposite markers.

All images, text and illustration(s) © Cascade Yarns® 2025







All images, text and illustration(s) © Cascade Yarns® 2025